

Part Number: C-132

High Power C-mount Multi-Mode Fabry-Perot CW Wavelength at 1650nm Lensed Options Available



### **Features**

- High Output Power
- High Dynamic Range
- High Efficiency
- Standard C-mount
- Cost Effective

### **Application**

- Laser Range Finder
- Target Illumination



SemiNex delivers the highest available power at infrared wavelengths between 12xx and 19xx nm. When necessary, we will further optimize the design of our InP & GaSb laser chips to meet our customers' specific optical and electrical performance needs. Diodes, bars and packages are tested to meet customer and market performance demands. Typical results and packaging options are shown. Contact SemiNex for additional details or to discuss your specific requirements.



## Specification

C-132



Optical	Symbol	Тур.	Units
Center Wavelength	λ <sub>c</sub>	1650	nm (±20)
Output Power (CW)*	P <sub>out</sub>	3.5	watts (±10%)
Emitter Width	W	95	μm
Spectral Width FWHM	Δλ	15	nm
Slope Efficiency	η	0.3	W/A
Fast Axis Div.	Θ⊥	28	deg FWHM
Slow Axis Div.	Θ	9	deg FWHM
Electrical	Symbol		Units
Power Conversion Eff.	η	13	%
Threshold Current	Ітн	0.5	Α
Operating Current	lop	13	Α
Operating Voltage	V <sub>op</sub>	1.7	V
Operating Voltage  Mechanical	V <sub>op</sub> Symbol	1.7 Range	V Units

\*Specified values are rated at a constant heat sink temperature of 20°C.

\*\*High temperature operation will reduce performance and MTTF.

Unless otherwise indicated all values are nominal.

#### \*Available Lenses

Suffix	Description	
-118	Lens Collimated <10mrad f=274μm, 5mm Lg	
-134	Lens Matched f=274μm, 5mm Lg	
-141	Lens, FAC, f=590μm, 5mm Lg, Collimated 5mrad	
-186	Lens, FAC, f=590μm, 5mm Lg, WD=50μm	




#### SemiNex Laser Diodes C-132


Graphs & Data

### Typical C-mount L-I-V Characteristics






## Typical C-mount Output Spectrum





### **Mechanical Drawing**





All statements, technical information and recommendations related to the product herein are based upon information believed to be reliable or accurate. The accuracy or completeness herein is not guaranteed, and no responsibility is assumed for any inaccuracies. The user assumes all risks and liability whatsoever in connection with the use of a product or its application. SemiNex Corporation reserves the right to change at any time without notice the design, specification, deduction, fit or form of its described herein, including withdrawal at any time of a product offered for sale herein. Users are encouraged to visit www.seminex.com for the latest data. SemiNex Corporation makes no representations that the products herein are free from any intellectual property claims of others. Please contact SemiNex for more information. 2024 SemiNex Corporation






### **Mechanical Drawing**

C-132-118

C-132-134

C-132-141

C-132-186



All statements, technical information and recommendations related to the product herein are based upon information believed to be reliable or accurate. The accuracy or completeness herein is not guaranteed, and no responsibility is assumed for any inaccuracies. The user assumes all risks and liability whatsoever in connection with the use of a product or its application. SemiNex Corporation reserves the right to change at any time without notice the design, specification, deduction, fit or form of its described herein, including withdrawal at any time of a product offered for sale herein. Users are encouraged to visit www.seminex.com for the latest data. SemiNex Corporation makes no representations that the products herein are free from any intellectual property claims of others. Please contact SemiNex for more information. 2024 SemiNex Corporation

