

60T4QCL 60W 24V 12/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead

Product datasheet

Technical data

General Product Information

Product number (Americas)	58729
Product name (Americas)	60T4QCL 60W 24V 12/CS 1/SKU
Lamp type	SINGLE END
Global order reference	60W 24V BA15D 1

Electrical Data

Nominal wattage	60 W
Nominal voltage	24.0 V

Photometric Data

Nominal luminous flux	1280 lm
Color temperature	3100 K
Color rendering index Ra	100

Physical Attributes & Dimensions

Lamp base	BA15d
Diameter (in)	0.567 in
Diameter	14.4 mm
Length	63.8 mm
Product weight	0.00 g

Lifetime Data

Nominal lifetime	500 hr
------------------	--------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	0046135587290
Declaration no. in SCIP database	In work

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Product datasheet

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
58729	0046135587290	FOLDING BOX	1	1.2 in x 1.2 in x 3.5 in	0.1 lb
58729	10046135587297	SHIPPING BOX	12	5.6 in x 4.5 in x 4.4 in	1.3 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.