

64250 HLX M/30 ESB 20W 6V 40/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead

Product datasheet

Technical data

General Product Information

| Product number (Americas) | 54261 | |
|---------------------------|---------------------------------------|--|
| Product name (Americas) | 64250 HLX M/30 ESB 20W 6V 40/CS 1/SKU | |
| ANSI code | ESB | |
| LIF code | M/33 | |
| Global order reference | 64250 HLX | |


Electrical Data

| Nominal wattage | 20 W |
|-----------------|------|
| Nominal voltage | 6 V |
| Type of current | AC |

Photometric Data

| Nominal luminous flux | 460 lm |
|----------------------------------|-------------------------|
| Illuminated field | 2.3*0.8 mm ² |
| Color temperature | 3350 K |
| Color rendering index Ra | 100 |
| Light center length (LCL) | 19.4 mm |
| Light center length (LCL) - (in) | 0.761 in |

Physical Attributes & Dimensions



| Lamp base | G4 |
|----------------|----------|
| Diameter (in) | 0.354 in |
| Diameter | 9 mm |
| Length | 31.0 mm |
| Product weight | 1.20 g |

Product datasheet

Operating Conditions

| Burning position | Any | |
|------------------|-----|--|
| | | |

Lifetime Data

| Nominal lifetime | 100 hr |
|------------------|--------|
| | |

Environmental & Regulatory Information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | |
|---|------------------------------------|--|
| Primary article identifier 4050300012407 | | |
| Declaration no. in SCIP database | No declarable substances contained | |
| Candidate list substance 1 | No declarable substances contained | |

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Packaging Information

| Product number | EAN/UPC | Packaging | Quantity | Outside dimensions l x w x h | Gross weight |
|----------------|---------------|--------------|----------|------------------------------|--------------|
| 54261 | 4050300012407 | FOLDING BOX | 1 | | |
| 54261 | 4050300890999 | SHIPPING BOX | 40 | 5.7 in x 4.2 in x 4.8 in | 0.4 lb |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.