

Multimode, Continuous Wave (CW)

Ontical Flectrical Characteristics \*\*

Optical Electrical Characteristics				
Parameter	Unit			
Wavelength	nm			
Operating Power	W			
Operating Current*	Α			
Operating Voltage	V			
Threshold Current	mA			
Slope Efficiency	W/A			
Vertical Far Field @FWHM	deg <sup>o</sup>			
Horizontal Far Field @FWHM	deg <sup>o</sup>			

<b>1W</b>				
Тур	Max			
830	-			
1	-			
1.5	1.7			
1.9	2.2			
500	700			
1	-			
30	-			
8	-			

**Absolute Maximum Ratings** 

Parameter	Unit	Condition	Min	Тур	Max
Operational Temperature***	оС	CW	-20	25	50

Please note that CW lasers may be damaged by excessive drive current or switching transients.



CT-830-1000-1XX

# **Features** &Options

- Gold-tin (AuSn) bonding, Cu submount
- Optional microlens
- Ultra low & high AR coating options

This datasheet is for general reference only. Specifications are subject to change without notice. Product subject to availability. Visit sheaumann.com or contact sales@sheaumann.com for more information on products and services.

## Safety Warning

Laser light emitted from any laser diode is invisible and may be harmful to the human eye. Avoid looking directly into the laser aperture when the device is in operation.

The use of optical instruments with this product will increase eye hazard.

The primary cause of diode failure is unexpected electrostatic discharge. To help prevent device failures, the user should always wear an ESD wrist strap, ground all applicable work surfaces and follow anti-static techniques when handling

## Operation Consideration

Operating the laser beyond the limits of the provided specifications may result in device failure or a safety hazard and will void warranty Devices must be passively or actively cooled in accordance with the provided specifications. Failure to comply with heatsinking requirements may result in device failure.

Due to the delicate nature of laser diodes, Sheaumann offers a limited warranty for all products. Please refer to our Terms and Conditions for full details.

## **Compliance Notice**

These products are intended solely as a component of an electronic product and are not certified in accordance with IEC 60825-1 or 21 CFR 1040.10/21 CFR 1040.11. These products are subject to Export

Administration Regulations (EAR) and will require a Destination Control Statement or End User Agreement for each sales order.









+1 508.970.0600

sheaumann.com

<sup>\*\*</sup> Data is based on CW operation at 25°C.

<sup>\*\*\*</sup> Device degradation accelerates with increased temperature.